DCode

DC-3RL



Printing Mode	thermal type
print width	72mm(effective printing width)
print density	576dot / line
print speed	Max 90mm/s
interface	USB+ Bluetooth
print paper width	80mm
roll diameter	50 mm
paper thickness	0.06-0.08mm
print command	Compatible with ESC/POS,TSPL,CPCL
character size	24*24 point and 12*24 point
bar code type	Code 39,DODE128,UPC-A,UPC-E,JAN13(EAN13),JAN8(EAN8),ITF,CODE93,CODEBAR,QR CODE
input buffer	10K Bytes
Power adapter	Input: AC100~240V; Output: DC9V/1A
Lithium battery	2600mAh/7.2V
Charging time	3 hours
Battery Life	500 times cycle charging
Working environment temperature	0 ℃~50℃, Humidity: 20%~85%
Storage environment temperature	-20℃~60℃， Humidity : 5%~95%
Mechanical Properties	50KM
Operating System	Android ,IOS ,(Win9x / Win2000 / WinNT / WinXP / ,WinVista , Win 7 , Win 8)
SDK	IOS and Android
Lanagues Code Page	CP-437 , CP-737 , CP-775 , CP-850 ,CP-852, CP-855 , CP-857 , CP-858 ,CP-860,CP-862,CP-863,CP-864,CP-865,CP-866 , CP-1251 ,CP-1252,CP-1253,CP-1254,CP-1255,CP-1256,CP-1257 (India language also , UTL-8)