* A 20-line scan omnidirectional pattern provides aggressive scanning as an additional benefit to hand presentation applications.
* The Orbit scanner has an engineered “sweet spot” to optimize scan performance and first pass read rate.
* An adjustable scan head enables users to tilt the scanner +65° for targeted scanning of larger products.



For 1D/2D Barcodes

DC-5132

(2D OMNIDIRECTIONAL)

HAND HELD
BARCODE SCANNER

The DCode Advantage

QUICK — DEPENDABLE — TOUGH

From the distribution centre to the point-of-sale, you need convenient, precise data capture. Regardless of your industry or the kind of barcode scanner you need, you'll be able to find it in our vast portfolio.

Our technology and constant innovation enhances customer experience, improves overall productivity/profitability and amplifies supply chain efficiency.

Future Proofing

2D barcodes have made their way to your point of Sale appearing on everything you are buying, from groceries to printed and digital Coupons/tickets. DC5132 delivers affordable scanning of 2D barcodes, allowing enterprises and individuals to meet their current and future barcode scanning needs with a single device.

Affordability and Simplicity delivered

Dc5132, the best-selling hands-free omnidirectional scanner of all time, presents an innovative, elegant and affordable solution for convenience retail applications where counter space is at a premium. DC5132 provides all the features you need to keep your workers productive: industry-leading scanning speed; true point-and-shoot scanning simplicity — no need to align barcode and scanner; and hands-free and handheld flexibility.

Exceptional Value for everyday use

Dc5132 offers an exceptional value for enterprises and individuals that require the versatility of area-imaging technology today or may need it in the future. Produced by a company with decades of experience in engineering quality data capture solutions, maybe your retail store has a trendy decor. Or maybe your counter space is extremely limited. The DC5132 sports a sleek contemporary design that is at home in either environment. And with the most compact footprint in this class, the DC5132 can fit in the most space constrained areas — from the POS in a boutique to the ticket window at a train station.

Proven Quality you can trust

Compact, lightweight and rugged, the Dcode scanner maximizes customer satisfaction and employee efficiency with a patented 20-line scan pattern, an easy-to-find sweet spot and a scan speed of 500 scans per second

When you buy DC5132, you get the additional affirmation of buying an item of global quality adhering to global standards of quality and use. It comes with a factory warranty of 1 Year to give you added peace of mind.

Application Scenarios : Retail chains • office automation • mail/parcel sorting • distribution

DC5132
OMNI-DIRECTIONAL
HANDS - FREE PRESENTATION IMAGERS

SPECIFICATION

Future Proofing

Product Specification:

IV-5132 2D Omni-directional Barcode Scanner

Scan Performance

Scanning type	DC-5132 2D Omni-directional
Optical resolution	640*480
Lighting source	red LED supplement
Scanning speed	500 times/s
Scanning angle	rotate Roll:0-360°, tilt pitch: ±65°, deflect SKEW: ±60°
Sweeping barcode type	paper, thin film medium one-dimensional; mobile phone, flat screen, etc.
Printing contrast	20%
Error rate	≤1/2,000,000
Interface type: USB:	USB:HID KEYBOARD (default mode), USB virtual serial port
IP level	up to IP5X standard
Prompt mode	buzzer sound prompt and green light prompt
Decode Capability	**1D**- 1D:Code 39, Full ASCII Code 39, Code 32, Code 128, Code 93,Code 11, Codabar/NW7, All UPC/EAN/JAN code (EAN-13,EAN-8, UPC-A, UPC-E, EAN-128), Interleave 2 of 5, STD 2of 5, Industrial 2 of 5, matrix 2 of 5, Chinese Postage Code,IATA, MSI/PLESSY, Italian Pharmacy Code, Industrial 2 of 5,BC-412 **2D**-QR Code, PDF417,Data Matrix

Electrical parameters

Electric voltage	4.5~5.5V DC V1 ± 5%
Working current	Max 130mA ; Operating 80mA
Optical safety certification	ICE4247* IEC60950
Electromagnetic compatibility	En55022, EN55024

Mechanical parameters

Size	104mm*96.3mm*166mm
Interface	USB(Option RS-232)
Cable length	150cm
Weight	300g
Drop	0.8m

Enviromental parameter

Working temperature	-20°C~50°C
Storage temperature	-20°C~70°C
Working humidity	0%~80%
Drop test	1.5m fall to concrete

Packing Details

* Standard list: Omini-directional Scanner*1, Cable *1, Manual *1, Box *1.
* Single package size: 182*123*111mm
* Single gross weight: 0.5kg
* 40pcs/CTN Carton Size: 519*400*577mm
* 40pcs/CTN Carton G.W.:19Kg, N.W:17Kg



© 2019 BBSPL.
All rights reserved – Copying or altering of this document is prohibited without express written consent of from BBSPL.
DCode logo is a registered trademark of BBSPL in India.
Products specifications are subject to change without notice

For More Information:

www.dcodeinternational.com